



Número da peça	d [mm]	D [mm]	W [mm]	Peso [g]	Velocidade [rpm]	Carga estática (kN)
6000HT500	10	26	8	20	2300	1.14
6001HT500	12	28	8	25	2090	1.37
6002HT500	15	32	9	30	1930	1.65
6003HT500	17	35	10	40	1790	1.88
6004HT500	20	42	12	69	1620	2.89
6005HT500	25	47	12	80	1375	3.38
6006HT500	30	55	13	120	1060	4.62
6007HT500	35	62	14	160	895	6.01
6008HT500	40	68	15	190	820	6.8
6009HT500	45	75	16	250	730	8.27
6010HT500	50	80	16	260	690	9.02
6011HT500	55	90	18	390	615	12.26
6012HT500	60	95	18	420	570	13.43
6013HT500	65	100	18	440	510	14.45
6014HT500	70	110	20	600	495	18.21
6015HT500	75	115	20	640	460	19.65
6016HT500	80	125	22	850	410	22.1
6017HT500	85	130	22	890	395	23.7
6018HT500	90	140	24	1150	375	27.6
6200HT500	10	30	9	30	2100	1.5

500°C high temperature bearings

6201HT500	12	32	10	37	1950	1.79
6202HT500	15	35	11	45	1650	2.17
6203HT500	17	40	12	65	1460	2.75
6204HT500	20	47	14	110	1225	3.79
6205HT500	25	52	15	130	1150	4.62
6206HT500	30	62	16	200	895	6.48
6207HT500	35	72	17	290	775	8.5
6208HT500	40	80	18	370	695	10.4
6209HT500	45	85	19	410	650	11.79
6210HT500	50	90	20	460	615	13.86