

Silicon Carbide Ceramic Bearings Metric Size



Número da peça	ID	OD	Largura	Tipo de escudo	Carga dinâmica	Carga estática	Velocidade máxima (X1K rpm)	Material do Anel	Faixa de temperatura	Precisão	Liberação	RoHS	ALCANCE
633	3 mm	13 mm	5 mm	Open	221 N	78 N	28	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
623 2RS	3 mm	10 mm	4 mm	Sealed	107 N	35 N	35	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
603 2RS	3 mm	9 mm	5 mm	Sealed	46 N	30 N	39.2	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
623	3 mm	10 mm	4 mm	Open	107 N	35 N	35	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
603	3 mm	9 mm	3 mm	Open	46 N	30 N	39.2	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
MR82x	2.5 mm	8 mm	2.5 mm	Open	95 N	29 N	42	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
MR82x 2RS	2.5 mm	8 mm	2.5 mm	Sealed	95 N	29 N	42	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
692x 2RS	2.5 mm	7 mm	3.5 mm	Sealed	66 N	21 N	44.1	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
692x	2.5 mm	7 mm	2.5 mm	Open	66 N	21 N	44.1	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
682x 2RS	2.5 mm	6 mm	2.6 mm	Sealed	36 N	12 N	49.7	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
602x	2.5 mm	8 mm	2.8 mm	Open	94 N	28 N	42	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
682x	2.5 mm	6 mm	1.8 mm	Open	36 N	12 N	49.7	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
602x 2RS	2.5 mm	8 mm	4 mm	Sealed	94 N	28 N	42	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
MR72 2RS	2 mm	7 mm	3 mm	Sealed	66 N	21 N	44.1	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
MR72	2 mm	7 mm	2.5 mm	Open	66 N	21 N	44.1	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
MR62 2RS	2 mm	6 mm	2.5 mm	Sealed	56 N	16 N	52.5	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
MR62	2 mm	6 mm	2.5 mm	Open	56 N	16 N	52.5	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
692 2RS	2 mm	6 mm	3 mm	Sealed	56 N	16 N	52.5	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
MR52	2 mm	5 mm	2 mm	Open	29 N	8 N	59.5	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
MR52 2RS	2 mm	5 mm	2.5 mm	Sealed	29 N	8 N	59.5	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
692	2 mm	6 mm	2.3 mm	Open	56 N	16 N	52.5	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant
682 2RS	2 mm	5 mm	2.3 mm	Sealed	29 N	8 N	59.5	Silicon Carbide	[-176 to 2192 °F]	ABEC-1	C0	Compliant	Compliant

Silicon Carbide Ceramic Bearings Metric Size

682	2 mm	5 mm	1.5 mm	Open	29 N	8 N	59.5	Silicon Carbide	□176 to 2192 °F	ABEC-1	C0	Compliant	Compliant
672	2 mm	4 mm	1.2 mm	Open	25 N	8 N	68.59999999999999	Silicon Carbide	□176 to 2192 °F	ABEC-1	C0	Compliant	Compliant
602 2RS	2 mm	7 mm	3.5 mm	Sealed	66 N	21 N	42	Silicon Carbide	□176 to 2192 °F	ABEC-1	C0	Compliant	Compliant
602	2 mm	7 mm	2.8 mm	Open	66 N	21 N	42	Silicon Carbide	□176 to 2192 °F	ABEC-1	C0	Compliant	Compliant
633 2RS	3 mm	13 mm	5 mm	Sealed	221 N	78 N	28	Silicon Carbide	□176 to 2192 °F	ABEC-1	C0	Compliant	Compliant
683	3 mm	7 mm	2 mm	Open	53 N	18 N	44.1	Silicon Carbide	□176 to 2192 °F	ABEC-1	C0	Compliant	Compliant
683 2RS	3 mm	7 mm	3 mm	Sealed	53 N	18 N	44.1	Silicon Carbide	□176 to 2192 °F	ABEC-1	C0	Compliant	Compliant
693	3 mm	8 mm	3 mm	Open	95 N	29 N	42	Silicon Carbide	□176 to 2192 °F	ABEC-1	C0	Compliant	Compliant